

RESIDENTIAL & COMMERCIAL

Mini 8 Series Sprinklers

Ideal for residential and light commercial appications, the Mini 8 provides great value and water efficiency when your landscape is too large for sprays but too small for a full-size rotor.



SIMPLICITY

Top arc indication ensures easy adjustments from 40° - 360°. Five interchangeable nozzles available.

CONVENIENCE

Part- and full-circle arcs in one sprinkler offer convenience and reduce inventory requirements. Ratcheting riser provides easy final arc adjustment.

VERSATILITY

Fills in that hard to cover 18' to 30' gap between spray heads and rotors.



SPECIFICATIONS

Mini 8 Series Sprinklers

SPECIFICATIONS

Lawn Pop-Up

- Radius: 20' 35' (6,1 10,7m)
- Flow Rate: 0.80 3.40 GPM (3,0 - 11,5 LPM)
- **Recommended operating pressure:** 30-50 psi (2,4 - 3,5 Bar)
- Maximum operating pressure: 60 psi (4,4 Bar)
- Body Diameter: 1 ³/₄" (44mm)
 Cap Diameter: 2 ¹/₄" (57mm)
- Height: 6" (150mm)
- 1/2" (13mm) threaded NPT inlet
- **Pop-up to nozzle:** 3 3/4" (95mm)

Nozzle Performance

 Lawn Pop-up Apex @ 40 psi (2,8 Bar)

	25°
Nozzle	Max. Height of Spray
0.75	3′11″ (0,95m)
1.0	5′1″ (1,55m)
1.5	6′7″ (2,04m)
2.0	7′6″ (2,32m)
3.0	7'6" (2,32m)

FEATURES

Operational

- Pressure activated seal and robust trip mechanism for enhanced reliability
- Trajectory: 25°
- Two-Year Warranty

Installation

- Five interchangeable nozzles (comes preinstalled with a 1.5 nozzle) to cover varying flow requirements
- Stainless steel radius adjustment screw allows up to 25% reduction
- Ratcheting riser for easy arc adjustment
- 1/2"' inlet covers smaller radius requirements
- Optional check valve holds back 8' elevation change




Arc Scale

Arc Adjustment

Use slot screwdriver to turn. Read arc change on the arc scale as the screwdriver is turned. The arrow points to the arc degrees.

Specifying Information



would be specified as: MINI8-4P-30